

## **BENEFITS**

- Absorbs sound created by fans inside the server cabinet
- Absorbs heat and maintain temperature
- Light weight & easy to install
- Adds quality to the cabinet in low prices
- Highly durable on long lasting
- Available with Fire Retardant ratings




Server Rack / Cabinet

**EGG TRAY Acoustic Foam** 



## **Technicals & Specs**

Size	6x3 Ft   1800x900mm   1.8x0.9m
Thickness	25mm   50mm   75mm   Upto 800mm
Material	Acoustic Polyurethane
Density	32 kg/m³   40 kg/m²   50 kg/mੈ
NRC ( noise reduction coefficient )	0.90 ( Tested by ARAI )
STC ( sound transmision coefficient )	22 Db
CFD Hardness 25% (kg)	23.50
CFD Hardness 65% (kg)	53.10
CFD Hardness C Factor	2.260
Resiliance	42%
Tensile	125 kpa
Elongation	100%
Application	Sound Absorption
Fire Rating	UL94
Chemical Components	Polyol   TDI
Frequency Absorption	Mid   High
Tile Size	1x1 Ft   2x2 Ft   3x3 Ft
Shelf Life	10 Years



## Figure 1 : NISAC of MMT Acoustix® acoustic foam at one third octave frequency band, Hz

## **ARAI TESTED & CERTIFIED**

This test report clearly specify that MMT Acoustix® Acoustic Foam absorbs 90% of the high & mid frequency sound waves. This test is conducted by ARAI, Pune.

www.mmtacoustix.in

